



2023/2024 Dodge Hornet SPECIFICATIONS

*Specifications are based on the latest product information available at the time of publication.
All dimensions are in inches (millimeters) unless otherwise noted.
All dimensions measured at curb weight with standard tires and wheels.*

LAYOUT

| | GT | R/T PHEV |
|-----------------|---------|----------|
| Number of seats | 5 | 5 |
| Drive type | AWD | eAWD |
| Chassis | Unibody | Unibody |

INTERNAL COMBUSTION ENGINES

| | Hurricane4 2.0-liter, 4-cylinder Turbo | 1.3-liter, 4-cylinder Turbo PHEV |
|-------------------|---|--|
| Fuel type | Gasoline | Gasoline Plug-in Hybrid |
| Cylinder capacity | 2.0-liter (1,995 cu. cm.) | 1.3-liter (1,332 cu. cm.) |
| Emission standard | EPA and CARB | EPA and CARB |
| Horsepower | 268 (premium fuel) | 288 Net Combined |
| Torque | 295 lb.-ft. (400 Nm) | 383 lb.-ft. Total Installed Front 199 lb.-ft. (ICE) Rear 184 lb.-ft. (e-Motor) |

TRANSMISSIONS

| | GT | R/T PHEV |
|------|--------------|--------------|
| Type | 9-speed Auto | 6-speed Auto |



ELECTRIC MOTORS

| | GT | R/T PHEV |
|--------------------|----|---|
| E-motor position | NA | P1, P4 |
| E-motor horsepower | NA | P1 BSG — 44 hp, P4 Rear — 121 hp (90 kW) |

BATTERY

| | GT | R/T PHEV |
|--|----------|---|
| Capacity | NA | 15.5 kWh |
| Chemistry | NA | Lithium-ion, nickel manganese cobalt graphite |
| Battery cooling | NA | Refrigerant Gas |
| Total voltage [V] | NA | 306 |
| Cell configuration (Series Parallel) | NA | 84S 1P |
| Battery weight | NA | 276 lbs. (125 kg) |
| Fuel economy [MPGe] | NA | TBC |
| City/Hwy/Comb | 21/29/24 | TBC |

PERFORMANCE

| | GT | R/T PHEV |
|-------------------|-----|----------|
| Stop/Start | Yes | Yes |
| Top Speed [mph] | 140 | 128 |
| 0 - 60 mph (sec.) | 6.5 | 5.6 |



DIMENSIONS—IN. (MM) UNLESS OTHERWISE NOTED

| | GT | R/T PHEV |
|--------------------------------|------------------------|------------------------|
| Length (L103) | 178 (4,528) | 178 (4,528) |
| Height | 63.8 (1,620) | 63 (1,601) |
| Width with mirrors | 82 (2,082) | 82 (2,082) |
| Wheelbase | 103.8 (2,636) | 103.8 (2,636) |
| Trunk volume | 27 cu.-ft. (765 L) | 22.9 cu.-ft. (650 L) |
| Trunk volume rear seats folded | 54.7 cu.-ft. (1,550 L) | 50.5 cu.-ft. (1,430 L) |
| Ground clearance | 8 (203) | 6.1 (156) |
| Front overhang | 37.4 (951) | 37.4 (951) |
| Rear overhang | 37 (941) | 37 (941) |
| Fuel tank capacity | 13.5 gal (51 L) | 11.2 gal (42 L) |

WEIGHT—LBS. (KG)

| | GT | R/T PHEV |
|-----------------|---------------|-----------------|
| Curb | 3,715 (1,600) | 4,140 (1,875) |
| Payload | 1,245 (565) | 1,195 (542) |
| Towing capacity | 2,000 (907) | 2,000 (907) |

BRAKES

| | GT | R/T PHEV |
|-----------------|---|---|
| Front | 12.08 (305) | Brembo calipers standard |
| Rear | 10.94 (278) | Brembo calipers standard |
| Brembo calipers | Front: 13.53 (345) Rear: 12.08 (305) | Front: 13.53 (345) Rear: 12.08 (305) |

SUSPENSIONS

| | GT | R/T PHEV |
|-------|--------------------------------|--------------------------------|
| Front | MacPherson strut (FSD damping) | MacPherson strut (FSD damping) |
| Rear | Chapman strut (FSD damping) | Chapman strut (FSD damping) |



STEERING

| | GT | R/T PHEV |
|--------------------|---------------------|---------------------|
| Power | Electric | Electric |
| Ratio | 13.6: 1 | 14.5: 1 |
| Turns lock-to-lock | 2.28 | 2.5 |
| Turning circle | 37.95 ft. (11.57 m) | 37.86 ft. (11.54 m) |

#